

# DuraTracker®

## Flowmeter

With the new DuraTracker flowmeter, we've built upon the market-leading 2100 portable logger by adding expanded capabilities into a proven product solution.

## Optimize flow monitoring, cost effectively.

The DuraTracker flowmeter is the most efficient and reliable flow monitoring solution on the market today for a wide range of open channel flow measurement applications. It supports flow measurement technologies including non-contact laser area velocity, submerged Doppler area velocity, and ultrasonic. The flowmeter calculates flow using standard open channel level-to-flow and area velocity conversions, user defined equations, level to area data points, or level to flow data points.

The DuraTracker package cost-effectively integrates cellular communications and multiple flow technologies within a single module. The standard Bluetooth capabilities make the programming, sensor calibration, and data retrieval job easy through wireless devices. A field upgradable remote cell phone communication option is also available.



For permanent applications without the battery compartment, the portable version comes with two compartments for off-the-shelf batteries and desiccant.



**DURA  
TRACKER**

### Applications:

- Collection system flow monitoring
- Surface water flow monitoring
- Industrial pretreatment flow monitoring
- WWTP flow monitoring

### Standard Features:

- Rugged, submersible enclosure meets IP68 environmental specs
- Quick connect plug-and-play multiple sensors connectivity: Ultrasonic, AV, and laser
- pH and sampler interface
- Bluetooth communication interface with wireless devices
- USB interface
- MODBUS output
- Replaceable high-capacity internal desiccant cartridge and Gortex filter protect sensor air reference port from water entry and internal moisture
- Variable data-rate storage
- Compatible with off-the-shelf batteries

## DuraTracker® Flowmeter Specifications

### Size (H x W x D):

**DuraTracker:** 12.25 x 6.25 x 12.75 in (31.12 x 15.88 x 32.39 cm)

### DuraTracker w/o Battery Box:

13.375 x 8.625 x 4.5 in (33.97 x 21.91 x 11.43 cm)

### Weight

**DuraTracker:** 14.3 lbs. (6.49 kg) without batteries

### DuraTracker w/o Battery Box:

5.3 lbs. (2.4 kg)

**Materials:** ABS, Delrin, Stainless Steel

**Enclosure:** IP68

### Temperature Range:

Operating: -40 to 140 °F (-40 to 60 °C)

Storage: -40 to 140 °F (-40 to 60 °C)

**Power Source:** 2 x Alkaline Lantern Batteries

(each bank) 8 x Alkaline D Cell Batteries

4 x Lithium Thionyl Chloride (Low Temperature Applications)

**Battery Life:** 310 Ex Ultrasonic Sensor: 18 months\*

(1 battery bank) 350 Ex AV Sensor: 8 months\*

360 Ex LaserFlow Sensor: 9 months\*

### Power Required

**DuraTracker:** 9–15 Vdc

**External Power:** 7–28 Vdc

## Built-in Conversions

### Flow Rate Conversions:

Up to 2 independent level-to-area conversions and/or level-to-flow rate conversions

### Level-to-Area Conversions:

Channel Shapes—round, U-shaped, rectangular, trapezoidal, elliptical, with tilt correction;  
Data Points—Up to 50 level-area points

### Level-to-Flow Conversions:

Most common weirs and flumes; Manning Formula;  
Data Points (up to 50 level-flow points); 2-term polynomial equation

### Total Flow Calculations:

Up to 2 independent, net, positive or negative, based on either flow rate conversion

## Optional Interfaces

**pH input** TIENet 301 pH Interface

**Sampler enabling** TIENet 306 sampler interface

\* Data shows 5 Parameter, 15 min data rate interval. Battery life determined by the number of devices and parameters logged. If a second bank of batteries is used, the battery life will double.

\* Turbidity > 20 NTU; Distance from liquid surface to bottom of sensor < 48 inches

\* Maximum non-linearity, hysteresis, and temperature error from actual liquid level

\* Uniform velocity profile

## Data Handling and Communications

**Data Storage:** Non-volatile flash; retains stored data during program updates. Capacity 8 MB (1.3 million readings or 2700 days with 5 parameters logged at 15 minute intervals; reports once per day).

**Data Types:** Level, velocity, flow rate 1, flow rate 2, flow rate 3, flow rate 4, total flow 1, total flow 2, total flow 3, total flow 4, input voltage, temperature

**Storage Mode:** Rollover; 5 bytes per reading Storage Interval: 15 or 30 seconds; 1, 2, 5, 15, or 30 minutes; or 1, 2, 4, 12, or 24 hours. Storage rate variable based on level, velocity, flow rate, total flow, or input voltage

### Communication Interface:

USB, Remote Cellular, Bluetooth,  
MODBUS ASCII/RTU

### Optional Cellular Communication:

LTE

## TIENet® Measurement Technologies

### TIENet 310 Ex Ultrasonic Level Sensor

**Level Measurement Range:** 0.3 to 3.3 m (1 to 11 ft)

**Level Accuracy:** ±0.006 m (0.02 ft) at ≤1 ft level change  
±0.012 m (0.04 ft) at >1 ft level change

### TIENet 350 Ex Area Velocity Sensor

**Velocity Measurement Range:** -1.5 to 6.1 m/s (-5 to 20 ft/s)

**Velocity Measurement:** Bi-directional

**Velocity Accuracy:** ±0.03 m/s (±0.1 ft/s) from -5 to 5 ft/s\*  
±2% of reading from 5 to 20 ft/s\*

**Level Measurement Range:** 0.01 to 3.05 m (0.033 to 10 ft)

**Level Accuracy:** ±0.10% Full Scale\*

### TIENet 360 LaserFlow (including Ex) Area Velocity Sensor

**Flow Accuracy:** ±4% of reading. (Typical, under normal flow conditions)

**Velocity Measurement Range:** -15 ft/s to 15 ft/s (-4.6 m/s to 4.6 m/s)

**Velocity Measurement:** Bi-directional\*

**Velocity Accuracy:** ±0.5% of reading ±0.03 m/s (0.1 ft/s)\*

**Level Measurement Range:** 0 to 3.05 m (0 to 10 ft)

**Level Accuracy:** ±0.006 m (0.02 ft) at ≤1 ft level change  
±0.012 m (0.04 ft) at >1 ft level change

## Multi-sensor Connectivity

4 TIENet devices of any combination of 350 Ex, 310 Ex, 306 or 301

1 TIENet 360/360 Ex and up to 3 other TIENet devices (350 Ex, 310 Ex, 306 or 301)