





# **PRODUCT CONFORMITY CERTIFICATE**

This is to certify that the

ISCO 5800 Automatic Waste Water Sampler

Manufactured by:

# Teledyne ISCO Inc.

4700 Superior Street Lincoln Nebraska NE 68504 USA

has been assessed by CSA Group and for the conditions stated on this certificate complies with:

Performance Standards and Test Procedures for Continuous Water Monitoring Equipment, Part 1: Performance standards and test procedures for Automatic Water Sampling Equipment, Environment Agency, version 4, April 2017

**Certification Ranges:** 

Lift height 0 to 6 meters

Project number: Certificate number: Initial certification: This certificate issued: Renewal date: 80174414 CSA MC130227/03 10 July 2013 07 July 2023 09 July 2028

Andrew Young Environmental Team Manager

MCERTS is operated on behalf of the Environment Agency by

## **CSA Group Testing UK Ltd**



Unit 6, Hawarden Industrial Park Hawarden, Deeside, CH5 3US Tel: +44 (0)1244 670 900

The MCERTS certificate consists of this document in its entirety. For conditions of use, please consider all the information within. This certificate may only be reproduced in its entirety and without change To authenticate the validity of this certificate please visit www.csagroupuk.org/mcerts

Page 1 of 5







#### **Certificate Contents**

Approved Site Application	2
Basis of Certification	
Product Certified	
Certified Performance	
Description	
General Notes	

## **Approved Site Application**

Any potential user should ensure, in consultation with the manufacturer, that the monitoring system is suitable for the intended application. For general guidance on monitoring techniques refer to the Environment Agency Monitoring Technical Guidance Notes available at <u>www.mcerts.net</u>

The product is suitable for use on applications for compliance with the Urban Wastewater Treatment Regulations.

#### **Basis of Certification**

This certification is based on the following Test Report(s) and on Sira's assessment and ongoing surveillance of the product and the manufacturing process:

WRc report	Report Reference: UC 7399 dated May 2007
WRc report	Report Reference: UC 9502 dated March 2013
WRc report	Report Number UC 13500 dated November 2018
CSA Sira	Evaluation report reference: 70171503 dated February 2019

## **Product Certified**

The 5800 automatic wastewater sampler consists of the following parts:

- 5800 control panel
- 5800 pump assembly
- 5800 distributor assembly
- 5800 refrigeration system

This certificate applies to all instruments fitted with software version 1.00.0006 onwards (serial number 213A00001 onwards).

CSA MC130227/03 07 July 2023

This certificate may only be reproduced in its entirety and without change To authenticate the validity of this certificate please visit www.csagroupuk.org/mcerts







#### **Certified Performance**

The instrument was evaluated for use under the following conditions:

Ambient Temperature Range: -10°C to +40°C

Test	Results		MCERTS specification
Sample Collection	Flow proportional and timed sampling available Certified for use with single 10 litre composite sample bottle and 24 X 1 litre bottles.		Clause 3.1.2
Sample interval	Sample interval range is 1 min to 99 hours, 59 minutes with increments of 1 min is selectable 4-20mA and pulse outputs are available 1min to 9,999 flow pulses with increments of 1 pulse.		Clause 3.1.2
Sample failure	Sample failures are recorded. Fault indicated on display		Clause 3.1.2
Sample line diameter	9.52 mm.		Clause 3.1.2 >9mm
Sample volume	Sample volume adjustable over the range 10 to 9,990ml in 1ml increments		Clause 3.1.2
Maximum volume of a discrete sample that can be set Total storage capacity both by numbers and volumes of individual bottles and in a composite container	9,990ml The following are available: 24 X 1 L PP or 350ml glass 4 X 10 L PE or glass 2 X 10 L PE or glass 1 X 20 L PE or glass 1 X 10 L PE or glass 24 X ProPak, 1 L wedge 1 X ProPak, 10 L round		Clause 3.1.2
Maximum sampling head	6 metres		Clause 3.1.2
Sample volume error – C.T.C.V Time proportional	Expanded uncertainty: 2.03% at 1m 3.29% at 3.5m 4.11% at 7m Overall: 3.14%	Mean error: 2.69% at 1m -2.46% at 3.5m -4.37% at 7m Overall: -1.38%	Clause 6.4.1.1 <5%

CSA MC130227/03 07 July 2023

This certificate may only be reproduced in its entirety and without change To authenticate the validity of this certificate please visit www.csagroupuk.org/mcerts







Test	Results		MCERTS specification
Sample volume – Contact time variable volume (CTVV) flow	Expanded uncertainty:	Mean error:	Clause 6.4.1.2
proportional sampling	2.46% at 1m	-0.03% at 1m	=0/
	1.69% at 3.5m	-1.05% at 3.5m	<5%
	1.31% at 7m	0.71% at 7m	
	Overall: 1.83%	Overall: -0.12%	
Sample volume – Constant volume variable time (CVVT) flow proportional sampling	Expanded uncertainty:	Mean error:	Clause 6.4.1.3
	1.77% at 1m	-0.04% at 1m	
	2.41% at 3.5m	-3.89% at 3.5m	<5%
	2.26% at 7m	-2.34% at 7m	
	Overall: 2.15%	Overall: -2.09%	
Analogue flow signal – Constant volume variable time (CVVT) flow proportional sampling	(	Clause 6.4.2.4 <1%	
Event Triggered Sampling	(	Clause 6.4.2.5 <1%	
Sample line velocity	0.95 m/s at	1m sampling head	Clause 6.4.3
	0.94 m/s at 2m sampling head		
	0.90 m/s at 3m sampling head		
	0.88 m/s at 4m sampling head		>0.5 m/s
	0.85 m/s at 5m sampling head		
	0.51 m/s at 6m sampling head		
Power Supply	3/8-inch	Clause 6.4.4.1	
103.5 VAC to 126.5 VAC	Min: 0.564m/s		>0.5m/s
	Ref: 0.57m/s		
	Max: 0.58m/s		
Sample integrity	No statistically significant for BOD, COD, suspend	Clause 6.4.5 Annex B5	
Sample timing	4	Clause 6.4.6 < ±10 sec/24h	
Ambient temperature effects	Expanded uncertainty:	Mean error:	Clause 6.4.7.2
a) volume	2.43% at −10°C	1.43% at -10°C	<5%
	2.58% at 40°C	3.04% at 40°C	<5%
Ambient temperature effects	During sample period:	24hrs after sample period:	Clause 6.4.7.3
b) temperature	4.1°C at -10°C	3.0°C at −10°C	Maintain sample
-, semperature	4.3°C at 20°C	3.8°C at 20°c	between
			0°C to +5°C

Certificate No: This Certificate issued: CSA MC130227/03 07 July 2023

This certificate may only be reproduced in its entirety and without change To authenticate the validity of this certificate please visit www.csagroupuk.org/mcerts







#### Description

The 5800 Refrigerated Sampler System consists of a 5800 Control Panel, 5800 Pump Assembly, 5800 Distributor Assembly, and 5800 Refrigeration System.

The 5800 Control Panel provides user programmable sampler features via a keypad and display. The 5800 Pump Assembly consists of a peristaltic pump for pulling samples to the sampler. The 5800 Distributor Assembly distributes the pumped sample into container(s) located in the refrigerator. The sample is transported by 3/8 inch I.D. PVC or PTFE lined suction line.

The refrigeration system utilizes a 1/4 hp compressor running on R134a refrigerant and is controlled by the microprocessor located in the 5800 Sampler Control Panel. The refrigerator cabinet is constructed from UV resistant LLDPE. The refrigeration system constructed from stainless steel and is powered by 230Vac 50 Hz.

#### General Notes

- 1. This certificate is based upon the equipment tested. The Manufacturer is responsible for ensuring that on-going production complies with the standard(s) and performance criteria defined in this Certificate. The Manufacturer is required to maintain an approved quality management system controlling the manufacture of the certified product. Both the product and the quality management system shall be subject to regular surveillance according to 'Regulations Applicable to the Holders of CSA Certificates'. The design of the product certified is defined in the CSA Design Schedule V01 for certificate No. Sira MC130227/02.
- 2. If the certified product is found not to comply, CSA Group should be notified immediately at the address shown on this certificate.
- 3. The certification marks that can be applied to the product or used in publicity material are defined in 'Regulations Applicable to the Holders of CSA Certificates'.
- 4. This document remains the property of CSA Group and shall be returned when requested by CSA Group.